BEER MEMBRANE FILTRATION BMF +FLUX 6

HIGHER BEER VOLUME IN A SMALLER FOOTPRINT

Specially designed for large breweries.

A fully automated filtration system for breweries that produce at a capacity between 200-900 hl/hour.

With our Pentair BMF +Flux 6, you save on waste disposal and product loss, benefit from measurable improvements in beer taste and contribute to sustainability.

BENEFITS

- Ideal for batch processing
- Reduce your beer loss down to 0,1%
- Helps achieve a sustainable operation
- Retain flexibility with system agility
- Benefit from in-house project management and engineering
- Contains a user-friendly start-stop system
- Remote access for 24/7 support, monitoring and optimization
- Fully automated
- Easy to add additive dosing units, a regenerable PVPP system, and membrane units for extra capacity
- Available on several software platforms



FEATURES

In-house:

- Pentair X-Flow Hollow Fiber Membrane Technology
- Pentair Südmo Process Valve Technology
- Pentair Haffmans Quality Control Measurement

SCOPE OF SUPPLY

- A complete turn-key beer filter line: standardized skid mounted units, integrated in an overall process control system
- Key units are an unfiltered beer tank, membrane units, a filtered beer tank and a unit for CO₂ dosing and blending to specified gravity
- SCADA system
- Electrical cabinet & chemical agents cabinet



KEY PERFORMANCE INDICATORS

Nominal capacity
Annual capacity
Turbidity
Oxygen pick-up
Beer loss, High gravity

200 - 900 HL/H Unlimited <0.8 EBC <25 ppb <0.2%

LEARN MORE

Interested and would you like to know more?

Click or scan our QR code to contact us or visit us at **PENTAIR.COM/BMF**

