

HAFFMANS RPC

REDPOST CHARGER/INTERFACE

GENERAL PRODUCT INFORMATION

Pasteurization reduces the number of microorganisms in beer and beverages which increases the product's shelf life. To maintain the quality of the product with regard to taste, smell, brightness, and color, pasteurization should be a gentle heat treatment. The most commonly used method of pasteurization makes use of a tunnel pasteurizer, through which containers, such as glass bottles and cans, travel while being sprayed with warm water. The effect of heat treatment in relation to time is expressed in pasteurization units (PUs).

The Redpost Charger/Interface, type RPC-50, charges the battery of the PUMonitor and is equipped with a PC and printer interface. Type RPC-80 has a printer interface that enables direct printing and works independent of a PC.

Redlink PC Software

After the pasteurization process is finished, the measurement stops and the PUs are immediately displayed on the PU-Monitor. When the monitor is connected to the Redpost Charger/Interface charging begins automatically. Subsequently, the measured values can be directly printed (RPC-80) and/ or passed on to a PC via an interface. The RedLink software processes the measured values and displays them in tabular and graphical format, which can be stored.



RPC-50



RPC-80

CUSTOMER BENEFITS

- **Maintenance free**
- **Stand-alone system (RPC-80)**

APPLICATIONS

- **Tunnel pasteurizer**
- **In combination with Redpost PU-Monitors**

HAFFMANS RPC

REDPOST CHARGER/INTERFACE

TECHNICAL DATA

RPC-50

Charging time

4 h (for full charge)

Interfaces

RS-232

Voltage

100 - 240 V AC / 50-60 Hz

Dimensions

190 x 130 x 105 (LxWxH mm)

Weight

530 g

Compatible with PU-Monitors

RPU-120+, RPU-351-353

RPC-80

Charging time

6 h (for full charge)

Interfaces

RS-232, USB for printing

Voltage

100 - 240 V AC / 50-60 Hz

Dimensions

310 x 240 x 105 (LxWxH mm)

Weight

4,5 kg

Compatible with PU-Monitors

All types

SCOPE OF SUPPLY

- Redpost Charger/Interface*
 - Type RPC-50
 - Type RPC-80
- PU-Monitor connecting cable
- Mains cable (Euro, US, UK or AUS plug)
- RedLink software set (CD + Interface)
- Printer cable (RPC-80)
- Instruction manual

* When ordering, please state which instrument you require.

OPTIONS

- Printer (RPC-80)



RPC-50

**HAFFMANS B.V.**

P.O. BOX 3150, 5902 RD VENLO, NETHERLANDS WWW.FOODANDBEVERAGE.PENTAIR.COM

All Pentair trademarks and logos are owned by Pentair. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

Pentair is an equal opportunity employer.

haffmans-redpost-charge-interface-2102-en ©2020 Pentair, All Rights Reserved.

